

# INERPRESS EN ISO 3821 N/L 20

According to EN ISO 3821

Designed for delivery of inert gases.

## Hose Construction

**Tube:** Black, smooth SBR rubber compound, resistant to inert gases. Not suitable for LPG

**Reinforcement:** Synthetic textile yarns

**Cover:** Smooth (/L), SBR/EPDM rubber compound resistant to abrasion, ageing



- For handling inert and noble gas
- Black cover following specs indication
- Excellent flexibility
- Burst Pressure Value 3:1






## Temperature Range

-25 °C (-13 °F) to +80 °C (+176 °F)

## Tolerances

According to EN ISO 3821

Refer to Technical Handbook on page TH34

Part Number				Working Pressure					in Stock
	I.D. (mm)	O.D. (mm)	MPa	psi	bar	kg/m	min. Bend Radius (mm)		
IH30412940/40	6.3	13.3	2.0	300.0	20	0.17	40	Y	
IH30413603/80	8	15	2.0	300.0	20	0.17	40	Y	
IH30412941/40	10	17	2.0	300.0	20	0.20	50	Y	

RUBBER HOSE – EN ISO 3821 – 2 MPa (20 bar) – I.D. MADE IN ITALY

 Parker with traceability code)

Distributed by:



Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu  
 Web: http://markuchi.eu/

România  
 Telephone/Fax : +40 21 780 45 58  
 E-mail: office\_ro@opwmarket.com  
 Web: http://furtunuri.eu/

Srbija  
 Telephone/Fax : 038111/2619-200  
 E-mail: office\_sr@opwmarket.com  
 Web: http://creva.eu/