

APERFLAT MB

Medium-duty, flat wrappable hose occupying a minimum amount of space, suitable for delivery under pressure of water and non-aggressive liquids in agriculture, in the building industry, in mining and in industry in general.

Hose Construction

Tube: Black, smooth PVC
 Reinforcement: Synthetic textile yarns
 Cover: Blue, highly abrasion and weather-resistant smooth PVC

Temperature Range

-15 °C (+5 °F) to +60 °C (+140 °F)



- Lay flat hose
- Cheaper alternative to PU for less demanding application
- Burst Pressure Value 3:1

Tolerances

Refer to Technical Handbook on page TH34

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH35653025/100	25	–	0.8	116.0	8	0.17	–	Y
IH35653032/100	32	–	0.8	116.0	8	0.21	–	Y
IH35653038/100	38	–	0.8	116.0	8	0.25	–	Y
IH35653040/100	40	–	0.8	116.0	8	0.26	–	Y
IH35653045/100	45	–	0.8	116.0	8	0.29	–	N
IH35653051/100	51	–	0.8	116.0	8	0.37	–	Y
IH35653063/100	63.5	–	0.8	116.0	8	0.46	–	Y
IH35653075/100	75	–	0.8	116.0	8	0.55	–	N
IH35653100/100	100	–	0.8	116.0	8	0.83	–	Y
IH35653150/100	150	–	0.3	43.5	3	1.25	–	Y
IH35653200/50	200	–	0.3	43.5	3	1.93	–	Y

APERFLAT MB DIAM. I.D. mm PARKER

Distributed by:



Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu
 Web: http://markuchi.eu/

România
 Telephone/Fax : +40 21 780 45 58
 E-mail: office_ro@opwmarket.com
 Web: http://furtunuri.eu/

Srbija
 Telephone/Fax : 038111/2619-200
 E-mail: office_sr@opwmarket.com
 Web: http://creva.eu/