

# GASTRUCK EN 1762 D-M

According to EN 1762

Liquid gas application (methane, propane, LPG) loading of tankers. According to EN 1762 (hoses and hose assemblies for LPG and natural gas).

## Hose Construction

Tube:	Low diffusion rate NBR rubber compound of uniform thickness
Reinforcement:	Synthetic textile fabrics, embedded built-in copper wire to facilitate the electrical connection between the hose and the end couplings
Cover:	Black, smooth, antistatic ( $R < 1 \text{ M}\Omega/\text{m}$ ), abrasion, oil, fuel and weather resistant NBR/SBR rubber compound. Pin-pricked to prevent the formation of blisters

## Temperature Range






-30 °C (-22 °F) to +70 °C (+158 °F)



- Electrical continuity guaranteed by copper wires if correctly assembled
- Low permeability
- Pin-pricked cover
- Burst Pressure Value 4:1

## Tolerances

On inside diameter	
≤ I.D. 38 mm	± 0.50 mm
> I.D. 38 mm	± 0.60 mm
On outside diameter	
≤ O.D. 52 mm	± 1.00 mm
> O.D. 52 mm	± 1.20 mm
Length tolerance	± 1 %

Part Number				Working Pressure					in Stock
	I.D. (mm)	O.D. (mm)	MPa	psi	bar	kg/m	min. Bend Radius (mm)		
IH30515071/40	13	23	2.5	362.5	25	0.40	80	N	
IH30515072/40	16	26	2.5	362.5	25	0.47	100	N	
IH36520580/40	19	31	2.5	362.5	25	0.61	160	Y	
IH36520581/40	25	38	2.5	362.5	25	0.83	200	Y	
IH36520582/40	32	45	2.5	362.5	25	1.00	250	Y	
IH36520583/40	38	52	2.5	362.5	25	1.27	320	Y	
IH36520584/40	50	66	2.5	362.5	25	1.84	400	Y	

RUBBER HOSE GASTRUCK – EN 1762 :2006 – Type D – I.D. mm – W.P. 25 bar – M – Quarter/Year MADE IN ITALY



Distributed by:

**DAIS** 

Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu  
 Web: http://markuchi.eu/

România  
 Telephone/Fax : +40 21 780 45 58  
 E-mail: office\_ro@opwmarket.com  
 Web: http://furtunuri.eu/

Srbija  
 Telephone/Fax : 038111/2619-200  
 E-mail: office\_sr@opwmarket.com  
 Web: http://creva.eu/