

ROBUR GPL

Liquid gas applications (methane, propane, LPG) in the loading and unloading of tankers and in the service stations.

Hose Construction

Tube: Low diffusion rate seamless extruded NBR rubber compound of uniform thickness.

Reinforcement: Two braids of high tensile steel wire

Cover: Black, SBR/CR rubber compound pin-pricked to prevent the formation of blisters, resistant to abrasion, oils, ozone and weathering

Temperature Range

-30 °C (-22 °F) to +70 °C (+158 °F)



- Suitable for vacuum application
- Low permeability
- Pin-pricked cover
- Burst Pressure Value 10:1

Tolerances

Length tolerance $\pm 1\%$

Part Number	Nominal Diameter		O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
	(mm)	(inch)		MPa	psi	bar			
IH36520560/0	6.5	¼	16.6	2.5	362.5	25	0.43	60	N
IH36520561/0	8	5/16	17.7	2.5	362.5	25	0.45	70	N
IH36520562/0	9.5	3/8	20.2	2.5	362.5	25	0.56	80	N
IH36520563/0	13	½	23.2	2.5	362.5	25	0.68	90	Y
IH36520564/0	16	5/8	26.5	2.5	362.5	25	0.80	95	Y
IH36520565/0	19	¾	30.5	2.5	362.5	25	1.03	100	Y
IH36520566/0	25	1	38.5	2.5	362.5	25	1.41	150	Y
IH36520567/0	32	1 ¼	45.6	2.5	362.5	25	1.82	200	Y
IH36520568/0	38	1 ½	52	2.5	362.5	25	2.00	280	Y
IH36520569/0	51	2	66.5	2.5	362.5	25	2.86	350	Y

ROBUR GPL I.D.mm W.P. bar – M – MADE IN ITALY

 Quarter/Year with traceability code

Distributed by:



Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/