



# AIRBRAKE DIN 74310

According to DIN 74310

Widely used in automotive air brake systems.

## Hose Construction

Tube:	Black, smooth EPDM nitrosamine free rubber compound
Reinforcement:	Stress-resistant, synthetic textile yarns
Cover:	Black, abrasion, ageing and weather-resistant, smooth EPDM nitrosamine free rubber compound



- Recommended DIN 74304 and DIN 74325 fittings and DIN 3017 clamps
- Automotive application
- Nitrosamine free compounds
- Burst Pressure Value 4:1








## Temperature Range

-40 °C (-40 °F) to + 70 °C (+158 °F)

## Tolerances

According to DIN 74310

Refer to Technical Handbook on page TH34

Part Number								in Stock
	I.D. (mm)	O.D. (mm)	MPa	psi	bar	kg/m	min. Bend Radius (mm)	
IH30315105/40	7	14	1.0	150.0	10	0.16	55	N
IH30315103/40	9	16	1.0	150.0	10	0.19	65	N
IH30315116/40	11	18	1.0	150.0	10	0.22	70	Y
IH30315115/40	13	25	1.0	150.0	10	0.49	100	Y
IH30315102/80 *	15	25	1.0	150.0	10	0.44	115	N

\*Not complying the norm

MADE IN ITALY  I.D. mm DIN 74310 – TÜV GEPRÜFT – Year/Quarter with traceability code

Distributed by:



Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu  
 Web: http://markuchi.eu/

România  
 Telephone/Fax : +40 21 780 45 58  
 E-mail: office\_ro@opwmarket.com  
 Web: http://furtunuri.eu/

Srbija  
 Telephone/Fax : 038111/2619-200  
 E-mail: office\_sr@opwmarket.com  
 Web: http://creva.eu/