



AIRBRAKE SAE J 1402-A

According to SAE J 1402-A

Widely used in automotive air brake systems.

Hose Construction

Tube:	Black, smooth, NBR/SBR rubber compound
Reinforcement:	Synthetic textile yarns
Cover:	Black, smooth, abrasion, ageing and weather-resistant CR rubber compound

Temperature Range

-40 °C (-40 °F) to + 93 °C (+200 °F)



- Tighter tolerances on ID and OD
- Automotive application
- Superior cover compound resistant to abrasion and weathering
- Burst Pressure Value 4:1

Tolerances

According to SAE J1402 – TABLE A
Refer to Technical Handbook on page TH34

Part Number	Nominal Diameter		O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
	(mm)	(inch)		MPa	psi	bar			
IH30315117/40	9.5	3/8	19	1.5	217.0	15	0.30	89	Y
IH30315119/40	12.7	1/2	22.2	1.5	217.0	15	0.37	102	Y
IH30315122/40	14.5	-	24.5	1.5	217.0	15	0.43	131	N
IH30315121/40	15.9	5/8	27	1.5	217.0	15	0.53	114	N

AIRBRAKE I.D. inch" (I.D. mm) SAE J 1402 – A – MADE IN ITALY



Distributed by:



Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/