



AIRBRAKE DIN 74310

Widely used in automotive air brake systems.

Hose construction

Tube: Black, smooth EPDM nitrosamine free rubber compound

Reinforcement: Stress-resistant, synthetic textile yarns

Cover: Black, abrasion, ageing and weather-resistant, smooth EPDM nitrosamine free rubber compound

Temperature Range

-40°C ÷ +70°C



- Recommended DIN 74304 and DIN 74325 fittings and DIN 3017 clamps
- Automotive application
- Nitrosamine free compounds
- Burst Pressure Value 4:1

According to

According DIN 74310

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R min mm
IH30315105/40	7	14	10	40	0,16	55
IH30315103/40	9	16	10	40	0,19	65
IH30315116/40	11	18	10	40	0,22	70
IH30315115/40	13	25	10	40	0,49	100
IH30315102/80	15	25	10	40	0,44	115

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses