



AIRBRAKE SAE J 1402-A

Widely used in automotive air brake systems.

Hose construction

Tube: Black, smooth, NBR/SBR rubber compound

Reinforcement: Synthetic textile yarns

Cover: Black, smooth, abrasion, ageing and weather-resistant CR rubber compound.

Temperature Range

-40°C ÷ +93°C



- Tighter tolerances on ID and OD
- Automotive application
- Superior cover compound resistant to abrasion and weathering
- Burst Pressure Value 4:1

According to

According SAE J 1402-A

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R min mm
IH30315117/40	9,5	19,0	20	62,1	0,30	89
IH30315119/40	12,7	22,2	20	62,1	0,37	102
IH30315122/40	14,5	24,5	20	62,1	0,43	131
IH30315121/40	15,9	27,0	20	62,1	0,53	114

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses