



## AUTOGENE EN ISO 3821 NB/L 20 (Blue)

Designed for delivery of welding and allied process gases.

### Hose constructon

**Tube:** Black, smooth SBR rubber compound, resistant to Welding Gases and not suitable for LPG, good resistance to ignition

**Reinforcement:** Synthetic textile yarns

**Cover:** Smooth (/L) or ribbed (/R), red (NR) or blue (NB), SBR/EPDM rubber compound resistant to abrasion, ageing, hot surfaces and incandescent particles

### Temperature range

-25 °C ÷ +80 °C



- For welding in industrial and domestic application
- Colored cover following specs indication: Red for Acetylene and Blue for Oxygen
- Exceeds the standard on backre test
- Excellent -exibility
- Burst Pressure Value 3:1

**According to**  
EN ISO 3821

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH30412703/40	6.3	13.3	20	60	0.15	40
IH30412706/40	6.3	16.3	20	60	0.25	40
IH30412915/100	8	15	20	60	0.17	40
IH30412707/40	9	16	20	60	0.19	45
IH30413220/40	10	17	20	60	0.20	50

### Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses