



## CARBOBLUE N/L 10

Carboblue is specially designed for applications where there is a requirement for extracting NOx (nitrogen oxide and its mixtures that emit polluted substances into the environment during air combustion) and dramatically reducing exhaust gas from diesel engines. These objectives are included in European parameters EURO IV and EURO V.

### Hose construction

**Tube:** Black, smooth, antistatic ( $R < 1 \text{ M/m}$ ) and sulphur free EPDM rubber compound nitrosamine free with peroxide curing.

**Reinforcement:** Synthetic textile fabrics

**Cover:** Black, smooth, antistatic ( $R < 1 \text{ M/m}$ ), EPDM rubber compound nitrosamine free, ageing, heat and weather resistant.

### Temperature Range

-40° to +100°C with peaks +120°C



- Compatibility approved by Ad-Blue manufacturer
- Environmental friendly
- Nitrosamine free
- Available HW version to defrost and keep additive at the right temperature
- Burst Pressure Value 3:1

### Tolerances

According UNI EN ISO 1307

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R min mm
IH30515030/100	16	23	10	30	0.27	100
IH30515031/80	19	27	10	30	0.37	115
IH30515032/50	25	36	10	30	0.68	150

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses