



## CARBOPRESS N/L 10

Suitable for fuel oils, petrol and diesel having an aromatic content not exceeded 50% and also for grease.

### Hose construction

**Tube:** Black, smooth, NBR rubber compound

**Reinforcement:** Synthetic textile yarns

**Cover:** Black, smooth, abrasion, oil, fuel, and weather-resistant, antistatic ( $R < 1 \text{ M/m}$ ) special NBR/EPDM rubber compound

### Temperature range

-25 °C (-13 °F) to +80 °C (+176 °F) up to +100 °C (+212 °F) for fuels



- Dual pressure lines
- Also suitable for water and air in general service applications
- Burst Pressure Value 3:1

**According to:**  
UNI EN ISO 1307

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R мин mm
IH30501001/100	5	12	10	30	0.12	40
IH30511003/100	6	12	10	30	0.11	50
IH30511002/100	6	13	10	30	0.14	50
IH30501002/100	8	15	10	30	0.17	65
IH30501003/100	10	17	10	30	0.20	80
IH30501004/100	13	20	10	30	0.24	105
IH30511004/100	16	23	10	30	0.29	130
IH30501006/40	19	27	10	30	0.39	150
IH30501007/50	25	35	10	30	0.63	200

### Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5  
1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses