




COOLING HOSE



For supplying coolant or air; Flexible, retaining any adjusted position, with threaded connector

Hose construction

1. rugged and non-corroding connecting thread (brass)
2. wide flat
3. long-life adjustable steel hose (nickel-plated)
4. sealing inner tube
5. robust steel drain spout



- flexible
- good resistance to alkalis and acids
- good resistance to chemicals
- good resistance to UV and ozone
- kink-proof
- retaining any adjusted position
- very robust
- conform to RoHS guideline

Temperature range

-20°C ÷ +70°C

No	Thread mm	Max length mm	Length of Thread mm	I.D. mm	Bend radius mm	Weight kg/m
950-0200-1210	R 1/8	200	9	3	50	0,080
950-0250-1210	R 1/8	250	9	3	50	0,100
950-0320-1210	R 1/8	320	9	3	50	0,120
950-0400-1210	R 1/8	400	9	3	50	0,150
950-0500-1210	R 1/8	500	9	3	50	0,190
950-0630-1210	R 1/8	630	9	3	50	0,240
950-0800-1210	R 1/8	800	9	3	50	0,300
951-0200-1210	R 1/4	200	9	5,5	60	0,120
951-0250-1210	R 1/4	250	9	5,5	60	0,150
951-0320-1210	R 1/4	320	9	5,5	60	0,180
951-0400-1210	R 1/4	400	9	5,5	60	0,230
951-0500-1210	R 1/4	500	9	5,5	60	0,280
951-0630-1210	R 1/4	630	9	5,5	60	0,350
951-0800-1210	R 1/4	800	9	5,5	60	0,450
952-0200-1210	R 3/8	200	9	7	70	0,180
952-0250-1210	R 3/8	250	9	7	70	0,220
952-0320-1210	R 3/8	320	9	7	70	0,280
952-0400-1210	R 3/8	400	9	7	70	0,350
952-0500-1210	R 3/8	500	9	7	70	0,430
952-0630-1210	R 3/8	630	9	7	70	0,540
952-0800-1210	R 3/8	800	9	7	70	0,680
953-0320-1210	R 1/2	320	9	8	75	0,330
953-0400-1210	R 1/2	400	9	8	75	0,400
953-0500-1210	R 1/2	500	9	8	75	0,500
953-0630-1210	R 1/2	630	9	8	75	0,620
953-0800-1210	R 1/2	800	9	8	75	0,780

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses