




CP HiTex 483

Suction and blast hose, especially suitable:

- for solids such as dust, powder and fibres
- for gaseous media such as vapors and smoke
- for de-dusting and suction plants, flue gas extraction, blast furnace exhaust and welding gas exhaust for exhaust gas technique, engine construction, engine warming, aircraft construction and military construction
- as bellows and compensator

Hose construction

1. clamp profile supporting spiral: all-stainless steel (INOX)
2. multi-layer hose wall wall: interior stainless steel wire reinforced and special coated glass fabric, thermo-insulation fabric, exterior special coated glass fabric
3. special thermal insulation layer



- multi-layer
- insulating
- extremely heat resistant
- flexible
- abrasion predection via external clamp profile

Temperature range

-60°C ÷ +900°C, with peaks up to +1100°C

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
483-0100-0000	100	114	0,130	0,180	114	2,800	6
483-0110-0000	110	124	0,120	0,160	124	3,050	3 6
483-0115-0000	115	129	0,118	0,150	129	3,180	3 6
483-0120-0000	120	134	0,115	0,140	134	3,310	3 6
483-0125-0000	125	139	0,110	0,120	139	3,430	3 6
483-0130-0000	130	144	0,105	0,110	144	3,560	3 6
483-0140-0000	140	154	0,100	0,090	154	3,820	3 6
483-0150-0000	150	164	0,070	0,075	164	3,070	3 6
483-0160-0000	160	174	0,065	0,070	174	3,270	3 6
483-0170-0000	170	184	0,065	0,065	184	3,460	3 6
483-0175-0000	175	189	0,065	0,060	189	3,550	3 6
483-0180-0000	180	194	0,060	0,055	194	3,650	3 6
483-0200-0000	200	214	0,060	0,045	214	4,030	3 6
483-0215-0000	215	229	0,055	0,040	229	4,320	3 6
483-0225-0000	225	239	0,055	0,040	239	4,510	3 6

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses



No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
483-0250-0000	250	264	0,040	0,035	264	4,990	3 6
483-0275-0000	275	289	0,040	0,030	289	5,470	3 6
483-0300-0000	300	314	0,035	0,025	314	5,950	3 6
483-0315-0000	315	329	0,035	0,025	329	6,150	3 6
483-0325-0000	325	339	0,030	0,150	339	6,550	3 6
483-0350-0000	350	364	0,025	0,015	364	6,910	3 6
483-0375-0000	375	389	0,025	0,015	389	7,250	3 6
483-0400-0000	400	414	0,025	0,010	414	7,870	3 6
483-0450-0000	450	464	0,020	0,010	464	8,830	3 6
483-0500-0000	500	514	0,020	0,010	514	9,790	3 6
483-0600-0000	600	614	0,015	0,005	614	11,720	3
483-0700-0000	700	714	0,010	0,005	714	13,640	3
483-0750-0000	750	764	0,010	0,005	764	14,600	3
483-0800-0000	800	814	0,010	0,005	814	15,560	3
483-0900-0000	900	914	0,010	0,002	914	17,480	3
483-1000-0000	1000	1014	0,010	0,001	1014	19,400	3

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses