




CP HiTex 485



- flexible hose/ ducting for hot and cold gases
- vehicle gas exhaust system, car gas extraction: hose reel, slotted floor channel, underfloor extraction system
- engine test bench, exhaust gas measurement
- high temperature extraction: oven, foundry, furnace, smelting, ceramics industry, glass industry, steel plant, aluminium mill
- bellows, compensators

Hose construction

- 1.clamp profile supporting spiral: galvanised steel
- 2.multi-layer hose wall; wall: interior and exterior special coated glass fabric



Temperature range

-60°C ÷ +500°C, with peaks up to +550°C



- secure clamping of the wall within the clamp profile
- highly flexible + compressible
- insulating
- suitable for light overpressure
- very good heat resistance
- conforms to RoHS guideline

No	I.D. inch / mm	O.D. mm	Pressure bar	Bending radius mm	Weight kg/m	Max length m
485-0100-0000	4 / 100-102	115	0,150	53,0	1,640	6
485-0110-0000	- / 110	125	0,130	57,0	1,790	3 6
485-0115-0000	4,5 / 114-115	130	0,120	59,5	1,860	3 6
485-0120-0000	4,72 / 120	135	0,110	61,0	1,940	3 6
485-0125-0000	5 / 125-127	140	0,100	62,5	2,020	3 6
485-0130-0000	- / 130	145	0,095	65,0	2,090	-
485-0140-0000	5,5 / 140	155	0,075	69,0	2,240	3 6
485-0150-0000	6 / 150-152	165	0,060	73,0	1,860	3 6
485-0160-0000	6,3 / 160	175	0,055	77,0	1,980	3 6
485-0165-0000	6,5 / 165	180	0,050	79,0	2,040	-
485-0170-0000	- / 170	185	0,050	81,0	2,100	3 6
485-0175-0000	- / 175	190	0,050	82,5	2,160	-
485-0180-0000	7 / 178-180	195	0,050	85,0	2,220	3 6
485-0200-0000	8 / 200-203	215	0,040	93,0	2,460	3 6
485-0215-0000	- / 215	230	0,035	98,5	2,670	-
485-0225-0000	- / 225	240	0,030	102,5	2,750	3 6
485-0228-0000	9 / 228-229	243	0,030	106,0	2,900	-

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses



No	I.D. inch / mm	O.D. mm	Pressure bar	Bending radius mm	Weight kg/m	Max length m
485-0250-0000	- / 250	265	0,030	113,0	3,050	3 6
485-0254-0000	10 / 254	269	0,025	114,5	3,110	-
485-0275-0000	- / 275	290	0,025	122,5	3,400	-
485-0280-0000	11 / 280	295	0,020	125,0	3,450	-
485-0300-0000	- / 300	315	0,020	133,0	3,640	3 6
485-0305-0000	12 / 305	320	0,020	135,0	3,710	-
485-0315-0000	- / 315	330	0,020	138,5	3,850	-
485-0325-0000	- / 325	340	0,015	142,5	3,940	-
485-0330-0000	13 / 330	345	0,015	144,5	4,000	-
485-0350-0000	- / 350	365	0,015	153,0	4,230	3 6
485-0356-0000	14 / 356	371	0,015	155,5	4,300	-
485-0375-0000	- / 375	390	0,015	162,5	4,530	-
485-0400-0000	- / 400	415	0,015	173,0	4,820	3 6
485-0406-0000	16 / 405-406	421	0,010	175,5	4,890	-
485-0450-0000	- / 450	465	0,010	193,0	5,410	3 6
485-0457-0000	18 / 457	472	0,010	196,0	5,490	-
485-0500-0000	- / 500	515	0,005	213,0	6,000	3 6
485-0508-0000	20 / 508	523	0,005	217,0	6,100	-
485-0600-0000	- / 600	615	0,005	253,0	7,190	3
485-0610-0000	24 / 610	625	0,005	257,0	7,310	-
485-0700-0000	- / 700	715	0,005	293,0	8,370	3
485-0712-0000	28 / 712	727	0,005	298,0	8,510	-
485-0750-0000	- / 750	765	0,003	313,0	8,960	-
485-0800-0000	- / 800	815	0,001	333,0	9,555	3
485-0815-0000	32 / 813-815	830	0,001	339,0	9,740	-
485-0900-0000	- / 900	915	0,001	373,0	10,740	3
485-0915-0000	36 / 915	930	0,001	379,0	10,920	-
485-1000-0000	- / 1000	1015	0,001	413,0	11,920	3
485-1016-0000	40 / 1016	1031	0,001	420,0	12,110	-

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses