



CP PTFE-INOX 475 CE




Suction and blast hose, especially suitable:

- for aggressive solids such as dust, powder and fibres
- for aggressive gaseous media such as vapors and smoke
- for de-dusting and suction plants
- for the chemical industry
- for the food and pharmaceutical industry

Hose construction

1. clamp profile supporting spiral: all-stainless steel (INOX)
2. wall: PTFE coated glass fabric



- surface resistance, PTFE film < 106 W
- very good heat resistance
- highly flexible + compressible 4:1
- abrasion protection via external clamp profile
- firm clamping of the wall in clamp profile
- anti-adhesive
- good resistance to alkalis and acids

Temperature range

-150 °C ÷ +250 °C; with peaks up to +270 °C

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bending radius mm	Weight kg/m
475-0050-0000	50	62	0,420	0,270	43	0,570
475-0055-0000	55	67	0,400	0,250	47	0,620
475-0060-0000	60	72	0,375	0,220	50	0,640
475-0065-0000	65	77	0,360	0,200	54	0,720
475-0070-0000	70	82	0,340	0,180	57	0,770
475-0075-0000	75	87	0,330	0,160	61	0,820
475-0080-0000	80	92	0,315	0,140	64	0,880
475-0090-0000	90	102	0,290	0,100	71	0,980
475-0100-0000	100	112	0,190	0,085	78	0,820
475-0110-0000	110	122	0,180	0,075	85	0,900
475-0115-0000	115	127	0,175	0,070	89	0,940
475-0120-0000	120	132	0,170	0,065	92	0,980
475-0125-0000	125	137	0,165	0,060	96	1,020
475-0130-0000	130	142	0,160	0,055	99	1,060
475-0140-0000	140	152	0,155	0,040	106	1,140
475-0150-0000	150	162	0,105	0,035	113	0,760
475-0160-0000	160	172	0,100	0,030	120	0,810
475-0170-0000	170	182	0,095	0,030	127	0,850
475-0175-0000	175	187	0,095	0,030	131	0,880
475-0180-0000	180	192	0,090	0,025	134	0,900
475-0200-0000	200	212	0,085	0,020	148	1,000

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses



No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bending radius mm	Weight kg/m
475-0215-0000	215	227	0,080	0,020	159	1,070
475-0225-0000	225	237	0,080	0,020	166	1,120
475-0250-0000	250	262	0,060	0,015	183	1,240
475-0275-0000	275	287	0,055	0,015	201	1,360
475-0300-0000	300	312	0,050	0,010	218	1,480
475-0315-0000	315	327	0,050	0,010	228	1,560
475-0325-0000	325	337	0,045	0,010	236	1,650
475-0350-0000	350	362	0,040	0,010	253	1,730
475-0375-0000	375	387	0,040	0,010	270	1,950
475-0400-0000	400	412	0,035	0,005	288	1,970
475-0450-0000	450	462	0,030	0,005	323	2,210
475-0500-0000	500	512	0,020	0,005	358	2,450
475-0600-0000	600	612	0,020	0,005	428	2,940
475-0700-0000	700	712	0,015	0,002	498	3,420
475-0750-0000	750	762	0,015	0,001	533	3,660
475-0800-0000	800	812	0,015	0,001	568	3,910
475-0900-0000	900	912	0,015	0,001	638	4,580
475-1000-0000	1000	1012	0,010	0,001	708	4,880

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses