



ELAFLON PLUS FEP D

As suction and discharge hose for barrels, containers, rail tankers, tankers and fixed installations. The steel helix ensures that the hose keeps in shape during suction and gravity operations, even with tight bending radius

Hose construction

Tube: Teflon® FEP, seamless, transparent, smooth bore. Intermed. Layer : adhesive rubber compound, grey

Reinforcement: two braids with crossed copper wires Intermed. Layer : EPDM, electrically conductive

Helix : galvanised spring steel (Form SD)

Cover: EPDM, electrically conductive, light grey, with OHM conductive stripe (up to DN 50) or black (DN 63-100). Abrasion and flame resistant, fabric impression, resistant against weather and ageing..

Temperature range

-20°C (-4°F) to +80°C (+176°F)



- Flexible
- Excellent chemical resistance

According to

EN 12115 and German safety standard TRbF 131/2.

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R min mm
FEPD13/40	13	23	16	25	0,4	100
FEPD19/40	19	31	16	25	0,6	125
FEPD25/40	25	37	16	25	0,9	150

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses