



EVA 373




Suction hose, especially suitable:

- for domestic and industrial vacuum cleaners
- for cleaning swimming pools

Hose construction

1. self-supporting profile design
2. open profile geometry wall: EVA



Temperature range

-45°C ÷ +65 °C



- light model
- highly flexible
- good resistance to alkalis and acids
- good resistance to UV and ozone
- gas and liquid tight
- crush-proof

No	I.D. mm	O.D. mm	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
373-0020-0000	20	26,8	0,500	52	0,130	-
373-0025-0000	25	32,2	0,500	66	0,150	-
373-0030-0000	30	38	0,500	77	0,200	-
373-0032-0000	32	40,4	0,500	82	0,240	30
373-0035-0000	35	43,8	0,500	88	0,260	-
373-0038-0000	38	47,2	0,500	93	0,310	30
373-0040-0000	40	49,4	0,500	100	0,320	-
373-0045-0000	45	55	0,500	111	0,370	30
373-0050-0000	50	60,4	0,500	122	0,440	30
373-0060-0000	60	72	0,500	143	0,670	-

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses