



FHD

Type FHD is a collapsible hose preferably used by naval forces. It can be reeled up flat, takes few place to stow away and is easy to handle. Used as pressure hose for all petroleum based products with an aromatic content up to 50 %, on bunkering ships, tankers as well as "flexible pipeline". Suitable for naval mobile supply and for offshore facilities.

Hose construction

Tube: NBR black, antistatic, no fuel-solubility
Reinforcement: Two low tensile textile braids
Cover: Chloroprene (CR), black, electr. conductive.

Temperature range

-20 °C ÷ +100 °C

Suction

Not for suction



According to

According to German military standart VG 95 955

Number/ Max length	ID mm	OD mm	WP bar	BP bar	Weight kg
FHD75/40	75	89	16	50	2,9
FHD100/40	100	116	16	50	3,8
FHD125/30	125	143	16	50	4,8
FHD150/30	150	170	16	50	5,8
FHD200/30	200	222	16	50	8,8

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses