



## FUCINO 10

Suitable for a variety of industrial applications, where a flexible and lightweight discharge hose for water and non-aggressive liquids are required.

Specifically designed for irrigation equipment and submersible pumps.

### Hose construction

**Tube:** Black, smooth SBR nitrosamine free rubber compound

**Reinforcement:** Synthetic textile fabrics

**Cover:** Black, abrasion, ageing and weather-resistant SBR nitrosamine free rubber compound



- Can be rolled at for easy transport and storage
- Resistant to Ozone and weathering
- Available in two different pressure rates
- Nitrosamine free
- Burst Pressure Value 3:1

### Temperature range

-30 °C ÷ +80 °C

### According to

RMA steel mandrel

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH36203251/40	25	31	10	30	0,38	-
IH36203253/40	32	38	10	30	0,47	-
IH36203240/40	38	45	10	30	0,65	-
IH36203255/40	40	47	10	30	0,68	-
IH36203256/40	45	52	10	30	0,75	-
IH36203257/40	50	57	10	30	0,83	-
IH36203258/40	60	67	10	30	0,99	-
IH36203263/20	100	108	10	30	1,78	-

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses