



GAMBRINUS RED SM 10

Recommended for wine, beer, liqueurs, fruit juice and soft drinks in process, package and transfer phase. Ideal either fixed and mobile installation. Not suitable for fatty food. Designed for suction and delivery.

Hose construction

Tube: White, smooth EPDM rubber compound, non-toxic, odorless and taste-free.

Manufactured on stainless steel mandrel for the maximum cleanliness and hygienic standards

Reinforcement: Synthetic textile fabrics and embedded steel wire helix

Cover: Red EPDM rubber compound, non-marking, abrasion and weather-resistant

Temperature range

-40 °C (-40 °F) to +120 °C (+248 °F)
sterilization at 110 °C for max 30 min.



- According to FDA, BfR class 2, DM 21/03/73, EC 1935/2004
- Up to 96 % alcoholic content
- Excellent exibility, kink resistance, easy handling
- ADI free
- Stainless Steel Fittings
- Burst Pressure Value 3:1
- Vacuum: 0.9 bar

According to
RMA steel mandrel

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH36242501/40	19	29	10	30	0.67	80
IH36242502/40	25	35	10	30	0.80	125
IH36242503/40	30	42	10	30	1.11	150
IH36242504/40	32	44	10	30	1.23	160
IH36242505/40	38	50	10	30	1.38	190
IH36242506/40	40	52	10	30	1.41	200
IH36242507/40	45	57	10	30	1.62	225
IH36242508/40	51	64	10	30	1.88	255
IH36242509/40	60	73	10	30	2.24	300
IH36242510/40	63.5	77	10	30	2.60	320
IH36242511/40	76	89	10	30	3.00	390
IH36242512/40	80	93	10	30	3.17	440
IH36242513/20	102	116	10	30	4.60	560

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses