



GASINOX /B0 /S

Hose for low pressure.

Hose construction

Maximum flexibility corrugated tube without braid

Quality of corrugated tube: AISI. 316

Temperature range

-200°C ÷ 800°C



| Number | ID mm | WP bar | TP bar | BP bar | R min mm | W Kg/m |
|------------|-------|--------|--------|--------|----------|--------|
| SSHCG20006 | 6 | 10 | 15 | 40 | 55 | 0,22 |
| SSHCG20010 | 10 | 10 | 15 | 40 | 60 | 0,33 |
| SSHCG20012 | 12 | 5,5 | 7.5 | 20 | 65 | 0,40 |
| SSHCG20015 | 15 | 5 | 7 | 18 | 70 | 0,50 |
| SSHCG20020 | 20 | 4.5 | 6 | 16 | 85 | 0,50 |
| SSHCG20025 | 25 | 4 | 6 | 16 | 95 | 0,65 |
| SSHCG20032 | 32 | 3 | 4.5 | 12 | 105 | 0,90 |
| SSHCG20040 | 40 | 2 | 3 | 8 | 150 | 1,10 |
| SSHCG20050 | 50 | 1 | 1,5 | 4 | 165 | 1,60 |
| SSHCG20065 | 65 | 1 | 1,5 | 4 | 200 | 1,90 |
| SSHCG20080 | 80 | 1 | 1,5 | 4 | 300 | 2,25 |
| SSHCG20100 | 100 | 0,7 | 1,1 | 3 | 350 | 3,10 |
| SSHCG20125 | 125 | 0,7 | 1,1 | 3 | 400 | 5,00 |
| SSHCG20150 | 150 | 0,5 | 0,75 | 2 | 550 | 5,80 |
| SSHCG20200 | 200 | 0,3 | 0,45 | 1.2 | 600 | 6,00 |
| SSHCG20250 | 250 | 0,25 | 0,36 | 1 | 850 | 7,50 |

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses