



GASINOX /B1

Hose for medium pressure.

Hose construction

Corrugated tube with 1 braid

Quality of corrugated tube: AISI. 316

Temperature range

-200°C ÷ 800°C



Number	ID mm	WP bar	TP bar	BP bar	R min mm	W Kg/m
SSHCG1006	6	170	257	690	75	0,33
SSHCG1010	10	158	227	604	90	0,48
SSHCG1012	12	113	174	452	100	0,60
SSHCG1015	15	95	136	494	105	0,70
SSHCG1020	20	90	133	348	115	0,75
SSHCG1025	25	72	120	308	125	0,95
SSHCG1032	32	52	83	238	150	1,40
SSHCG1040	40	48	67	182	200	1,75
SSHCG1050	50	40	61	186	275	2,45
SSHCG1065	65	32	56	138	350	3,00
SSHCG1080	80	28	40	128	400	3,55
SSHCG1100	100	20	32	86	500	4,80
SSHCG1125	125	16	24	64	660	7,50
SSHCG1150	150	11	16	40	760	9,10
SSHCG1200	200	8	12	32	1.020	10,5
SSHCG1250	250	6	9	24	1.220	12,05

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses