



## GASINOX /B2

Hose for high pressure.

### Hose construction

Corrugated tube with 2 braids

Quality of corrugated tube: AISI. 316

### Temperature range

-200°C ÷ 800°C



Number	ID mm	WP bar	TP bar	BP bar	R min mm	W Kg/m
SSHCG2006	6	305	452	1100	75	0,45
SSHCG2010	10	260	380	880	90	0,65
SSHCG2012	12	206	304	804	100	0,80
SSHCG2015	15	160	240	650	110	0,91
SSHCG2020	20	150	230	600	115	1,00
SSHCG2025	25	115	185	460	125	1,25
SSHCG2032	32	89	133	356	150	1,95
SSHCG2040	40	72	108	288	200	2,45
SSHCG2050	50	50	72	192	275	3,40
SSHCG2065	65	41	61	164	350	4,20
SSHCG2080	80	38	57	152	400	5,00
SSHCG2100	100	30	51	130	500	6,70
SSHCG2125	125	26	38	100	660	10,2
SSHCG2150	150	20	30	80	760	12,7
SSHCG2200	200	14	21	56	1.020	15,5
SSHCG2250	250	12	19	50	1.220	18,0

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses