



GASSOFLEX EGE 10

For delivery and/or suction of a wide range of chemical products compatible with polypropylene in cistern trucks, railcars or fixed deposits.

Hose construction

Inner helix: Polypropylen (E)

Outer helix: Galvanized steel (G)

Inner layer: Polypropylen (E).

Layers: Polypropylen.

Temperature range

-20 °C ÷ +100 °C

Pressure

GASSOFLEX EGE 10 – 10 bar



- Galvanized steel
- The working pressure is based on a safety factor of 5:1

Suction

0,8 bar

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R min mm
EGE1012	32	-	10	50	0,97	74
EGE1015	38	-	10	50	1,30	105
EGE1020	50	-	10	50	2,01	190
EGE1025	63	-	10	50	2,90	225
EGE1030	75	-	10	50	3,40	290
EGE1040	100	-	10	50	5,95	320

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses