



GASSOFLEX EGE 14

For delivery and/or suction of a wide range of chemical products compatible with polypropylene in cistern trucks, railcars or fixed deposits.

Hose construction

Inner helix: Polypropylen (E)

Outer helix: Galvanized steel (G)

Inner layer: Polypropylen (E).

Layers: Polypropylen.

Temperature range

-20 °C ÷ +100 °C

Pressure

GASSOFLEX EGE 14 – 14 bar



- Galvanized steel
- The working pressure is based on a safety factor of 5:1

Suction

0,8 bar

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R min mm
EGE1410	25	-	14	70	0,75	68
EGE1415	38	-	14	70	1,30	105
EGE1420	50	-	14	70	2,01	190
EGE1425	63	-	14	70	2,90	225
EGE1430	75	-	14	70	3,40	290
EGE1440	100	-	14	70	5,95	320

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses