



## GASSOFLEX GGE 7

Gassoflex GGE is recommended for use in delivery and/or suction of fuels, oils and lubricants in cistern trucks, railcars or fixed deposits.

### Hose construction

**Internal metallic helix:** Galvanized steel (G)

**External metallic helix:** Galvanized steel (G)

**Inner layer.** Polypropylen (E).

**Layers.** Polypropylen.

### Temperature range

-20 °C ÷ +100 °C



- Suction - 0,8 bar
- Working pressure 7bar
- The working pressure is based on a safety factor of 5:1

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R мин mm
GGE0720	50	-	7	35	1,81	180
GGE0730	75	-	7	35	3,06	270
GGE0740	100	-	7	35	5,35	305

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses