



GASSOFLEX SGE 10

For delivery and/or suction of a wide range of chemical products compatible with any polypropylene or stainless steel which may not come in contact with the external part of the hose. It is used in cistern trucks, railcars and fixed deposits.

Hose construction

Inner helix: Stainless steel (S)

Outer helix: Galvanized steel (G)

Inner layer. Polypropylene (E).

Layers. Polypropylen.

Temperature range

-20 °C ÷ +100 °C

Pressure

GASSOFLEX SGE 10 – 10 bar



- Stainless steel
- The working pressure is based on a safety factor of 5:1

Vacuum

0,8 bar

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R min mm
SGE1010	25	-	10	50	0,85	68
SGE 1012	32	-	10	50	1,07	74
SGE 1015	38	-	10	50	1,50	105
SGE 1020	50	-	10	50	2,00	190
SGE 1025	63	-	10	50	3,05	225
SGE 1030	75	-	10	50	3,55	290
SGE 1040	100	-	10	50	6,40	320

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses