



## GASSOFLEX SGT 14

For delivery and/or suction of a wide range of highly aggressive chemical products due to its inner lining of P.T.F.E. and is normally used in applications where the external wire spiral of galvanized steel does not come in contact with the product, being a cheaper alternative. It is used in cistern trucks, railcars and fixed deposits.

### Hose construction

**Inner helix:** Stainless steel (S)

**Outer helix:** Galvanized steel (G)

**Inner layer:** P.T.F.E. (T).

**Layers:** Polypropylen.

### Temperature range

-20 °C ÷ +100 °C

### Pressure

GASSOFLEX SGT 14 – 14 bar

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R min mm
<b>SGT1440</b>	100	-	14	70	6,40	320



- Stainless steel
- The working pressure is based on a safety factor of 5:1

### Vacuum

0,8 bar

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses