



GASSOFLEX SSE 10

For delivery and/or suction of a wide range of chemical products compatible with any polypropylene and stainless steel which may come in contact with the hose both internally or externally in tank trucks, railcars or fixed deposits.

Hose construction

Inner helix: Stainless steel (S)

Outer helix: Stainless steel (S)

Inner layer. Polypropylen (E).

Layers. Polypropylen.

Temperature range

-20 °C ÷ +100 °C

Pressure

GASSOFLEX SSE 10 – 10 bar



- Stainless steel
- The working pressure is based on a safety factor of 5:1

Suction

0,8 bar

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R min mm
SSE1010	25	-	10	50	0,85	68
SSE1012	32	-	10	50	1,07	74
SSE1015	38	-	10	50	1,50	105
SSE1020	50	-	10	50	2,00	190
SSE1025	63	-	10	50	3,05	225
SSE1030	75	-	10	50	3,55	290
SSE1040	100	-	10	50	6,40	320

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses