



## GST II Black 15

In agriculture, construction, air tool lubricant systems and general industrial for air (including oil mist), mild chemicals and water. Suitable for MRO and OEM channel. Not to be used with oil or refined fuel.

### Hose construction

**Tube:** Black EPDM, antistatic rubber compound

**Reinforcement:** Synthetic textile yarns.

**Cover:** Black, smooth EPDM rubber compound resistant to abrasion, heat and ozone



- Nitrosamine free
- Permanent fittings capability
- EPDM compound suitable also for oil mist
- Burst Pressure Value 4:1

### Temperature range

-40 °C ÷ +100 °C

### According to

UNI EN ISO 1307

Number	I.D.	O.D.	WP	BP	Weight	R min
	mm	mm	bar	bar	kg	mm
IH709319200/40	5	11	15	45	0.10	40
IH709325200/100	6.5	13	15	45	0.13	50
IH709331200/100	8	15	15	45	0.16	65
IH709338200/100	9.5	17	15	45	0.20	75
IH709350200/100	13	21	15	45	0.29	105
IH709363200/100	16	25	15	45	0.36	130
IH709375200/40	19	28	15	45	0.49	150
IH7093100200/40	25	36	15	45	0.69	200
IH7093125204/40	32	45	15	45	1.15	230
IH7093150204/40	38	52	15	45	2.76	250

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses