



## IDRO 10

Suitable for discharge of water and nonaggressive liquids, for agricultural uses, also in industrial facilities and on building sites.

### Hose construction

**Tube:** Black, smooth SBR nitrosamine free rubber compound

**Reinforcement:** Synthetic textile fabrics

**Cover:** Black: abrasion, ageing and weather-resistant SBR nitrosamine free rubber compound

### Temperature range

-30 °C ÷ +80 °C

### Vacuum

< I.D. 80 mm: 0,5 bar

≥ I.D. 80 mm: 0,3 bar



- Robust construction
- Resistant to twisting
- Nitrosamine free
- Burst Pressure Value 3:1

**According to**  
RMA steel mandrel

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH36203000/40	25	34	10	30	0,63	250
IH36203002/40	30	41	10	30	0,92	300
IH36203003/40	32	44	10	30	1,07	320
IH36203004/40	35	48	10	30	1,26	350
IH36203005/40	38	52	10	30	1,46	380
IH36203006/40	40	54	10	30	1,52	400
IH36203008/40	45	61	10	30	2,00	450
IH36203010/40	50	68	10	30	2,49	500
IH36203011/40	60	82	10	30	3,63	600
IH36203013/20	70	93	10	30	4,34	700
IH36203015/20	80	103	10	30	4,88	800
IH36203017/20	100	125	10	30	6,33	1000

## Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses