



IR IRRIGATION PU

A standard duty irrigation hose for water discharge and transfer in agricultural applications.

Hose construction

Polyurethane extruded through one woven polyester ply of reinforcement

Temperature range

-40 °C ÷ +80 °C



- Much easier to couple, install and remove than polyethylene pipe
- High performing polymer preserve from uid contamination
- Excellent resistance to abrasion
- Burst Pressure Value 2:1

| Number | I.D. mm | O.D. mm | WP bar | BP bar | Weight kg | Min R mm |
|---------------|------------|------------|-----------|-----------|--------------|-------------|
| IR20X200MB/60 | 51 | 55.6 | 31 | 62 | 0,41 | - |
| IR25X200MB/60 | 63.5 | 68.1 | 31 | 62 | 0,58 | - |
| IR30X200MB/60 | 76 | 82.6 | 24 | 48 | 0,75 | - |
| IR35X200MB/60 | 90 | 96.6 | 17 | 34 | 0,97 | - |
| IR40X200MB/60 | 102 | 108.6 | 17 | 34 | 1,14 | - |
| IR45X200MB/60 | 114 | 120.6 | 17 | 34 | 1,25 | - |
| IR50X200MB/60 | 127 | 133.6 | 17 | 34 | 1,42 | - |
| IR60X200MB/60 | 152 | 161.1 | 20 | 40 | 1,72 | - |

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses