



## LMD

Solvent hose 'Blue Band' for most solvents, paints (also water based), water lacquer, petroleum products, alcohols, aldehydes, esters and ketones. In short term operation also suitable for aromatic and chlorinated hydrocarbons.

### Hose construction

**Lining:** NBR special compound, blue, smooth, seamless, antistatic, conductive

**Reinforcements:** Textile braids

Type LMS additionally with galvanised steel helix

**Cover:** NBR / PVC special compound, conductive. From DN 63 chloroprene (CR ), black, conductive

### Temperature range

-20° up to + 80° C, short term up to + 100° C.

New lining : water resistant. Lower risk of discolouration. Open steam cleaning up to 130° C / max. 30 min.



- For most solvents, paints (also water based), water lacquer, petroleum products, alcohols, aldehydes, esters and ketones.

**According to**  
EN 12115

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R min mm
LMD09/40	9	22	16	25	0,3	50
LMD13/40	13	22	16	25	0,4	70
LMD19/40	19	31	16	25	0,6	100
LMD25/40	25	37	16	25	0,8	150

## Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses