



LPG

'Orange Band' Liquid Petroleum Gas hose to EN 1762. For propane, butane, and their mixtures to EN 589. As the hose lining is resistant to diffusion the hose is also suitable for natural gas. Not suitable for ammonia.

Hose construction

Lining: Nitrile rubber (NBR), black, electrically conductive, diffusion resistant

Reinforcements: Textile braids with 2 crossed tinned copper strands

Cover: Chloroprene (CR), black, electrically conductive, flame and abrasion resistant, ozone, UV and ageing resistant

Temperature range°

-40°C to +70°C



- As reel hose for supplies to domestic and industrial storage tanks, as pump hose for vehicle refuelling, for bulk loading and unloading from rail tankers, road tankers and ships.

According to

EN1762

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R мин mm
LPG010/40	10	19	25	100	0,8	0,3
LPG013/40	13	23	25	100	0,5	0,4
LPG019/40	19	31	25	100	0,5	0,6
LPG025/40	25	38	25	100	0,4	0,8
LPG032/40	32	45	25	100	0,3	1,0
LPG038/40	38	52	25	100	0,2	1,2
LPG050/40	50	66	25	100	0,2	2,0
LPG075/40	75	93	25	100	-	3,4
LPG100/40	100	118	25	100	-	4,3
LPG150/30	150	173	25	100	-	7,9
LPG200/30	200	128	25	100	-	11,0

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses