



## MULTIGASPRESS EN ISO 3821 NRA/L 20

Suitable for all fuel gases included in the EN ISO 3821 Norm (except fluxed fuel gases) like: acetylene, LPG, MPS, natural gas, methane.

### Hose constructon

**Tube:** Black, smooth NBR rubber compound suitable for all fuel gases included in the EN ISO 3821 Norm except fluxed fuel gases

**Reinforcement:** Synthetic textile yarns

**Cover:** Red/orange, PVC/NBR, smooth rubber compound. Resistant to ageing, weathering, pin-pricked cover to prevent blisters during use

### Temperature range

-30 °C (-22 °F) to +70 °C (+158 °F)



- Pin-pricked cover
- Low permeation
- Dual colored cover following specs indication
- Flexible hose for easy handling
- Burst Pressure Value 3:1

**According to**  
EN ISO 3821

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH30412960/40	6.3	13.3	20	60	0.17	50
IH30412962/40	9	16	20	60	0.21	70
IH30412964/40	12.5	22.5	20	60	0.41	105
IH30412965/40	16	26	20	60	0.44	150

### Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses