



NORFLEX® PVC 440




Pressure hose, especially suitable:

- for compressed air
- for gaseous and liquid media

Hose construction

1. fabric reinforced wall
2. smooth interior and exterior wall: soft PVC



- highly flexible
- smooth interior and exterior
- fabric reinforced
- cadmium free
- good resistance to alkalis and acids
- good resistance to chemicals
- good resistance to UV and ozone

Temperature range

-20°C ÷ +60°C

No	I.D. mm	Wall Thickness mm	O.D. mm	Pressure bar	Bending radius mm	Weight kg/m	Length m
440-9040-0000	4	3	10	20	15	0,086	50
440-9050-0000	5	3	11	17	20	0,098	50
440-9060-0000	6	3	12	15	25	0,110	50
440-9080-0000	8	3	14	15	30	0,135	50
440-9080-2174	8	2,5	13	13	30	0,107	-
440-9090-0000	9	3	15	12	35	0,147	50
440-9100-0000	10	3	16	10	50	0,159	50
440-9120-0000	12	4,5	21	12	65	0,303	50
440-9120-2175	12	3	18	10	65	0,184	-
440-9125-0000	12,5	3	18,5	10	65	0,190	50
440-9125-2174	12,5	2,5	17,5	8	65	0,153	-
440-9130-0000	13	3,5	20	10	75	0,236	50
440-9160-0000	16	4	24	10	100	0,327	50
440-9190-0000	19	4	27	7	125	0,376	50
440-9250-0000	25	4,5	34	6	150	0,542	25
440-9300-0000	30	4	38	5	200	0,555	25
440-9320-0000	32	5	42	5	250	0,755	25
440-9380-0000	38	5	48	4	300	0,878	25
440-9500-0000	50	5	60	3	450	1,123	25

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses