



## NORFLEX® SIL 408




Pressure hose, especially suitable:

- for solids
- for gaseous and liquid media

### Hose construction

1. wall interior and exterior smooth  
wall: silicone 60 ± 5 Shore A



### Temperature range

-60°C ÷ +180°C



- highly flexible
- smooth interior and exterior
- food grade wall, complies with: FDA 21 CFR Part 177.2600 / BGW
- small bending radius
- gas and liquid tight

No	I.D. mm	Wall Thickness mm	O.D. mm	Weight kg/m	Max length m
408-9020-0000	2	1	4	0,011	50
408-9020-2163	2	2	6	0,030	50
408-9030-0000	3	1	5	0,015	50
408-9030-2163	3	2	7	0,037	50
408-9030-2182	3	1,5	6	0,025	50
408-9040-0000	4	1	6	0,019	50
408-9040-2163	4	2	8	0,045	50
408-9040-2182	4	1,5	7	0,031	50
408-9050-0000	5	1	7	0,022	50
408-9050-2182	5	1,5	8	0,036	50
408-9060-0000	6	1,5	9	0,042	50
408-9060-2163	6	2	10	0,059	50
408-9070-0000	7	1,5	10	0,047	50
408-9080-0000	8	1	10	0,033	50
408-9080-2163	8	2	12	0,074	50
408-9080-2175	8	3	14	0,111	50
408-9090-0000	9	2	13	0,082	50
408-9100-0000	10	2	14	0,089	50
408-9100-2174	10	2,5	15	0,111	50
408-9120-0000	12	2	16	0,104	50
408-9120-2175	12	3	18	0,167	25
408-9150-0000	15	3	21	0,200	25
408-9160-0000	16	3	22	0,211	25
408-9200-0000	20	3	26	0,266	25
408-9250-0000	25	3	31	0,311	25

### Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5  
1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses