




## NORPLAST® PVC 112



For electrical installations, installation in switchboard plant, switch cabinets and mechanical engineering; as suction and pressure hose for gaseous and liquid media.

### Hose construction

NORPLAST full plastic conduit; hard plastic spiral integrated in the wall; wall: high grade soft PVC; spiral: rigid PVC



- smooth interior (easy retraction of cables)
- flexible
- gas and liquid tight
- good resistance to alkalis and acids
- good resistance to chemicals
- good resistance to UV and ozone
- light weight
- insulating

### Temperature range

-20 °C to +70 °C (short time +80 °C).

Number	I.D. Mm	O.D. mm	connector mm	W kg	Мин R mm
112-3010-9000	7	10	10	0,05	15
112-3014-9000	10	14	14	0,06	21
112-3017-9000	13	17	17	0,07	26
112-3019-9000	15	19	19	0,10	29
112-3021-9000	16	21	21	0,12	32
112-3027-9000	21	27	27	0,20	41
112-3036-9000	29	36	36	0,25	54
112-3045-9000	38	45	45	0,38	68
112-3056-9000	48	56	56	0,48	84

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses