



NORPLAST® PVC 379 GREEN SUPERELASTIC



Special suction and transport hose, especially suitable:

- for irrigation, liquid manure conveying, sewer and sink cleaning
- for fertilizers, insecticides, purifying agents

Hose construction


hard plastic spiral integrated in wall

spiral: rigid PVC

smooth interior

wall: low temperature flexible

soft PVC



- medium-heavy model
- smooth interior and exterior
- flexible
- good resistance to alkalis and acids
- good resistance to chemicals
- good resistance to UV and ozone

Temperature range

-25°C ÷ +60 °C

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
379-0019-0000	19	24	5,000	0,600	106	0,205	-
379-0020-0000	20	25	5,000	0,600	110	0,210	50
379-0025-0000	25	30	5,000	0,600	140	0,270	50
379-0032-0000	32	38	4,000	0,600	180	0,350	50
379-0038-0000	38	44	4,000	0,600	210	0,470	50
379-0040-0000	40	46	3,000	0,500	220	0,510	50
379-0050-0000	50	58	3,000	0,500	270	0,700	50
379-0051-0000	51	59	3,000	0,500	275	0,710	-

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses