



NORPLAST® PVC 388 SUPERELASTIC



Special suction and transport hose,
especially suitable:

- for industry, agriculture and construction engineering

Hose construction

hard plastic spiral


integrated in wall

spiral: rigid PVC

smooth interior

wall: high grade low temperature flexible soft

PVC



- flexible
- good resistance to alkalis and acids
- good resistance to chemicals
- good resistance to UV and ozone
- gas and liquid tight

Temperature range

-25°C ÷ +60 °C

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
388-0020-0000	20	25	1,000	0,500	40	0,190	25
388-0025-0000	25	31	1,000	0,500	45	0,230	50
388-0030-0000	30	36	1,000	0,500	55	0,280	-
388-0032-0000	32	38	1,000	0,500	60	0,300	50
388-0035-0000	35	41	1,000	0,500	65	0,340	-
388-0038-0000	38	45	1,000	0,500	70	0,390	50
388-0040-0000	40	47	0,800	0,500	70	0,420	50
388-0045-0000	45	52	0,750	0,500	80	0,510	-
388-0050-0000	50	58	0,700	0,400	85	0,620	50
388-0060-0000	60	68	0,650	0,400	100	0,740	50
388-0063-0000	63	71	0,650	0,350	105	0,780	50
388-0070-0000	70	79	0,500	0,350	120	0,890	-
388-0076-0000	76	85	0,400	0,350	130	1,010	50
388-0080-0000	80	90	0,350	0,350	135	1,150	50
388-0090-0000	90	101	0,300	0,300	150	1,350	-
388-0102-0000	102	114	0,280	0,300	170	1,590	25
388-0110-0000	110	122	0,250	0,300	185	1,830	-
388-0120-0000	120	132	0,200	0,300	200	2,000	-
388-0127-0000	127	139	0,200	0,250	210	2,130	25
388-0152-0000	152	164	0,180	0,250	250	2,950	25

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses