

ORINOCO

Abrasion resistant softwall hose, used for the delivery of sand or cast steel shot. It is manufactured with an antistatic rubber compound.

Hose construction

Tube: black, smooth, antistatic SBR/NR rubber, abrasion resistant.

Reinforcement: high strength synthetic cord.

Cover: black, smooth, (wrapped finish) antistatic SBR/NR rubber, abrasion resistant.



- Antistatic rubber hose for sand blast, abrasion resistant.
- Working pressure 10bar
- According to ISO 4649: 70+/- 5mm3.

Temperature range

-40°C to +70°C

Number	ID mm	OD mm	WP bar	Burst pressure bar	Weight kg/m	Max lenght m
1435612	13	25,5	10	30	0,40	120
1435620	16	29,5	10	30	0,53	120
IH36820300	19	32,5	10	30	0,60	120
IH36820200	25	40	10	30	0,84	120
IH36820201	30	45	10	30	0,94	120
IH36820202	32	48	10	30	1,10	120
IH36820303	38	52	10	30	1,09	120
IH36820305	40	60	10	30	1,63	120
IH36820206	51	69,5	10	30	1,85	120
IH36820207	60	80	10	30	2,29	120
1371290	63,5	83,5	10	30	2,48	120
1439740	65	83,5	10	30	2,28	120
IH36820209	80	103	10	30	3,61	120
IH36820211	102	122	10	30	3,71	120

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses