



PERFORMER AD10H

Hydraulic suction or discharge of abrasive materials.

Hose construction

Tube: wear resistant NR, black, smooth

Reinforcement: synthetic textile with embedded steel helix.

Cover: weather resistant EPDM, black, corrugated, fabric impression.

Electrical properties: conductive tube and cover.

Temperature range

-30°C to + 70°C

Couplings/Fittings

Hoses can be fitted with:

- 2 cuffed ends,
- 1 cuff + 1 END-FLEX® flange,
- 2 enlarged or smooth cuffs.

Hoses are fitted with END-FLEX® flanges (fitted hoses are allowed to work with pressure and vacuum mentioned in the table).



- Excellent resistance to abrasion.
- Low installation costs.
- Suppression of pressure surges.
- Reduction in pressure head loss.
- Damping of vibrations and noise.
- Many types of fittings possible.
- Excellent weather resistance.
- Vacuum 0.9bar

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
AD10H-32/20	32	60	10	30	2.6	160
AD10H-40/20	40	73	10	30	3.5	200
AD10H-50/20	50	83	10	30	4.2	250
AD10H-65/20	65	98	10	30	5.1	325
AD10H-75/20	75	108	10	30	5.7	375
AD10H-80/20	80	113	10	30	5.9	400
AD10H-100/20	100	133	10	30	7.3	500
AD10H-125/20	125	158	10	30	8.6	750
AD10H-150/20	150	183	10	30	10.4	1050
AD10H-175/10	175	208	10	30	11.9	1300
AD10H-200/12	200	234.5	10	30	14.6	1600
AD10H-250/12	250	285.5	10	30	17.5	2000
AD10H-300/12	300	340.5	10	30	24.8	2500
AD10H-350/12	350	391	10	30	30.6	3000
AD10H-400/12	400	441	10	30	36	4000
AD10H-500/12	500	548	10	30	53.3	5000

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses