



PERFORMER AR10

Hydraulic discharge of abrasive products.

Hose construction

Tube: wear resistant NR, black, smooth.

Reinforcement: two steel cords for ID ≤ 400 mm, four steel cords for ID ≥ 450 mm.

Cover: weather resistant EPDM, black, fabric impression.

Temperature range

- 30°C to + 70°C. Peaks up to +80°C.



- Excellent resistance to abrasion.
- Low installation cost.
- Suppression of pressure surges.
- Reduction in pressure head loss.
- Damping of vibrations and noise.
- Outstanding dimensional stability under pressure.
- Good resistance to kinking.
- Excellent weather resistance.

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
AR10-100/15	100	126	10	30	6.8	700
AR10-125/12	125	155	10	30	9.4	870
AR10-150/12	150	180	10	30	11.1	1050
AR10-175/10	175	205	10	30	12.7	1220
AR10-200/12	200	234	10	30	16.1	1400
AR10-250/12	250	283	10	30	20	1750
AR10-300/12	300	333	10	30	23.8	2100
AR10-350/12	350	390	10	30	33.8	2450
AR10-400/12	400	440	10	30	38.3	2800
AR10-450/12	450	508	10	30	64.3	3600
AR10-500/12	500	558	10	30	70.9	4000

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses