



PERFORMER GL AD10H

Hydraulic suction or discharge of abrasive materials.

Hose construction

Tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: weather resistant EPDM, black, corrugated, fabric impression.

Temperature range

- 30°C to + 70°C



- Excellent resistance to abrasion.
- Can be supplied cut to length for on-site coupling.
- Quick and easy installation.
- Light weight and low bending radius.
- Electrical conductivity ensured by the helix.
- Suppression of pressure surges.
- Reduction in pressure head loss.
- Damping of vibrations and noise.
- Excellent weather resistance.
- Vacuum 0.9bar

Couplings/Fittings

Hoses are fitted with BLOC-END® and must be used to the following maximum working pressure:

ID ≤ 150 mm: WP = 10 bar,

ID > 150 mm: WP = 5 bar.

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
TL0128511/20	25	53	10	30	2	125
TL0128512/20	32	60	10	30	2.3	160
TL0128513/20	40	73	10	30	3.4	200
TL0061620/20	50	83	10	30	4	250
TL0061621/20	65	98	10	30	5	325
TL0061622/20	80	113	10	30	5.9	400
TL0061623/20	100	133	10	30	7.1	500
TL0061624/20	125	158	10	30	8.7	750
TL0061625/20	150	183	10	30	10.2	1050
TL0061626/12	200	234.5	10	30	14.3	1600
TL0061627/12	250	285.5	10	30	18.9	2000
TL0061628/12	300	340.5	10	30	25.3	2500
TL5501488/12	350	391	10	30	31.5	3100
TL5601787/12	400	441	10	30	36.4	4000

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses