



PROTAPE® PUR-INOX 330 MHF-AS




Abrasion-proof and antistatic suction and blast hose, especially suitable:

- for transporting inflammable bulk materials and in areas liable to contain explosive mixtures
- for abrasive solids such as dust, powder, fibres and chips
- for gaseous media such as vapors and smoke
- for de-dusting and suction plants
- for the food and pharmaceutical industry

Hose construction

1. spring steel wire integrated in wall spiral: stainless steel wire (INOX)
2. extruded tape wall: permanently antistatic premium etherpolyurethane (Pre-PUR®)
3. wall thickness 0.6 mm approx.



- super-light and reinforced model
- highly flexible + compressible 3:1
- abrasion-proof
- optimized flow properties
- high tensile strength and tear resistant
- odourless and tasteless

According to

- EU Directive 2002/72/EC, incl. the latest Amending Directive 975/2009/EC

Temperature range

-40°C ÷ +90°C, with peaks up to +125°C

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
330-0040-1018	40	47	1,015	0,300	47	0,280	
330-0050-1018	50	58	0,815	0,260	58	0,360	10
330-0060-1018	60	68	0,680	0,210	68	0,430	10
330-0065-1018	65	73	0,630	0,180	73	0,470	
330-0070-1018	70	78	0,585	0,150	78	0,500	
330-0075-1018	75	83	0,545	0,140	83	0,530	
330-0080-1018	80	88	0,510	0,130	88	0,570	10
330-01 00-1018	100	108	0,410	0,090	108	0,660	10
330-01 20-1018	120	128	0,340	0,075	128	0,790	
330-01 25-1018	1 25	133	0,330	0,060	133	0,820	10
330-0150-1018	150	158	0,275	0,055	158	0,980	10
330-0160-1018	160	168	0,255	0,050	168	1,040	
330-0200-1018	200	208	0,205	0,040	208	1,290	10

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses