



PROTAPE® PVC 310



Universal suction and blast hose,
especially suitable:

- for powdery solids such as dust, powder and fibres
- for gaseous media such as vapors and smoke
- for air conditioning and ventilation technique

Hose construction

spring steel wire integrated in wall extruded tape
wall: high grade soft PVC
wall thickness 0.6 mm approx.

Temperature range

-20 °C ÷ +70 °C; with peaks up to +80 °C



- excellent value for money
- super-light model
- highly flexible + compressible 3:1
- optimized flow properties
- good resistance to alkalis and acids

According to

- German TRBS 2153 (formerly BGR 132), the spiral can be earthed

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bending radius mm	Weight kg/m	Max length m
310-0030-0000	30	37	0,670	0,200	37	0,240	5 10
310-0032-0000	32	39	0,630	0,200	39	0,260	5 10
310-0035-0000	35	42	0,580	0,190	42	0,280	5 10
310-0038-0000	38	45	0,550	0,185	45	0,300	-
310-0040-0000	40	47	0,510	0,180	47	0,320	5 10
310-0045-0000	45	52	0,460	0,165	52	0,350	5 10
310-0050-0000	50	58	0,410	0,155	58	0,310	5 10
310-0055-0000	55	63	0,370	0,140	63	0,330	5 10
310-0060-0000	60	68	0,340	0,120	68	0,360	5 10
310-0065-0000	65	73	0,315	0,105	73	0,390	5 10
310-0070-0000	70	78	0,290	0,090	78	0,420	5 10
310-0075-0000	75	83	0,270	0,085	83	0,450	5 10
310-0080-0000	80	88	0,255	0,075	88	0,470	5 10 15
310-0090-0000	90	98	0,230	0,065	98	0,530	5 10
310-0100-0000	100	108	0,205	0,050	108	0,570	5 10 15
310-0110-0000	110	118	0,185	0,045	118	0,620	5 10
310-0115-0000	115	123	0,180	0,045	123	0,650	5 10
310-0120-0000	120	128	0,170	0,045	128	0,680	5 10
310-0125-0000	125	133	0,165	0,035	133	0,710	5 10
310-0130-0000	130	138	0,160	0,035	138	0,730	-
310-0140-0000	140	148	0,150	0,035	148	0,790	5 10
310-0150-0000	150	158	0,140	0,035	158	0,840	5 10
310-0160-0000	160	168	0,130	0,030	168	0,870	5 10
310-0170-0000	170	178	0,120	0,030	178	0,950	-

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses



No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bending radius mm	Weight kg/m	Max length m
310-0175-0000	175	183	0,120	0,030	183	0,980	-
310-0180-0000	180	188	0,115	0,025	188	1,000	5 10
310-0200-0000	200	208	0,105	0,025	208	1,110	5 10
310-0215-0000	215	223	0,095	0,020	223	1,190	-
310-0225-0000	225	233	0,090	0,015	233	1,250	-
310-0250-0000	250	258	0,080	0,010	258	1,390	5 10
310-0275-0000	275	283	0,075	0,010	283	1,500	-
310-0280-0000	280	288	0,075	0,010	288	1,550	-
310-0300-0000	300	309	0,070	0,010	309	1,950	5 10
310-0315-0000	315	324	0,065	0,010	324	2,050	-
310-0325-0000	325	334	0,065	0,005	334	2,110	-
310-0350-0000	350	359	0,060	0,005	359	2,270	-
310-0375-0000	375	384	0,055	0,005	384	2,430	-
310-0400-0000	400	409	0,045	0,005	409	2,590	-
310-0450-0000	450	459	0,045	0,005	459	2,910	-
310-0500-0000	500	510	0,040	0,005	510	4,710	-

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses