



PROTAPE® TPE 326 MEMORY




Special exhaust gas hose, especially suitable:

- for suction of engine exhaust gas
- for hose reel
- for slotted floor channels
- for above and below floor suction extraction

Hose construction

1. special plastic-profile supporting spiral
2. fabric-reinforced tape wall: EPDM/ PP coated fabric
3. wall thickness 0.4 mm approx.



- vibration resistant
- crush-proof
- highly flexible + compressible
- flow-optimizing exterior folds
- fabric reinforced
- good resistance to chemicals
- small bending radius

Temperature range

÷ +200°C

No	I.D. mm	O.D. mm	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
326-0050-0000	50	67	0,400	80	0,410	-
326-0051-0000	51	68	0,400	82	0,420	15
326-0063-0000	63	80	0,280	101	0,510	15
326-0076-0000	76	93	0,170	111	0,610	15
326-0080-0000	80	97	0,130	116	0,640	-
326-0100-0000	100	117	0,050	120	0,780	-
326-0102-0000	102	119	0,050	122	0,800	15
326-0125-0000	125	142	0,035	144	0,970	-
326-0127-0000	127	144	0,035	152	0,980	15
326-0150-0000	150	167	0,030	180	1,150	-
326-0152-0000	152	169	0,030	182	1,160	15
326-0200-0000	200	217	0,010	240	1,500	-
326-0203-0000	203	220	0,010	244	1,520	15

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses