

## PUERTORICO

Hardwall hose used for the suction and delivery of petroleum products with aromatic content up to 30%.

### Hose construction

**Tube:** black, smooth, NBR rubber.

**Reinforcement:** high strength synthetic cord, antistatic copper wire, and steel helix wire.

**Cover:** black, smooth (wrapped finish), synthetic rubber, weathering and oil resistant.

### Temperature range

-20°C to +70°C



- suction and delivery of petroleum products
- Vacuum 0,9bar
- Working pressure 10bar

Number	ID mm	OD mm	WP bar	Burst pressure bar	Weight kg/m	Bending radius mm	Vacuum bar	Max lenght m
IH36530099	19	29	10	30	0,55	80	0,9	120
IH36531004	25	35	10	30	0,68	105	0,9	120
IH36531012	32	42	10	30	0,83	135	0,9	120
IH36531002	38	49	10	30	1,08	165	0,9	120
IH36530203	40	51	10	30	1,13	170	0,9	120
IH36530205	51	62	10	30	1,49	230	0,9	120
IH36531001	63,5	76	10	30	2,29	290	0,9	120
IH36530208	76	89	10	30	2,76	360	0,9	120
IH36531003	90	105,5	10	30	4,02	450	0,9	120
IH36530211	102	118	10	30	4,65	515	0,9	120

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses