



## PULSOR 125

Concrete pump hose for boom transfer, placement. Also for mortar, grout, slurry, and pneumatic discharge of cement and minerals.

### Hose construction

**Tube:** wear resistant NR, black, smooth.

**Reinforcement:** two steel cords plies for ID ≤ 65 mm and four steel cords plies for ID ≥ 76.2 mm.

**Cover:** wear and weather resistant NR, black, fabric impression.

### Temperature range

-30 °C ÷ +80 °C

### Couplings/Fittings

Swaged couplings with dimensions according to VICTAULIC or concrete pump manufacturers (PUTZMEISTER, SCHWING ...).



- Highly abras. resistant hose to give extended service life.
- Flexible and easy to handle.
- Robust construction to withstand heavy compressive loads to guarantee maximum safety.
- Construction eliminates kinking and allows easy cleaning by reverse pumping.
- Vacuum 0.8

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
TL0060005/20	50	68	70	125	2,24	200
TL0060007/20	65	85	70	125	3,88	250
TL0060418/20	76.2	101	70	125	4.96	270
TL0060420/20	101.6	129	70	125	7.08	300
TL0060422/20	125	156	70	125	9.83	360
TL0060423/20	150	185	70	125	13.34	570

## Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses