



PULSOR 170

High pressure concrete pump hose for boom transfer, placement. Pneumatic discharge of cement and minerals. Pumping of slurry and drilling mud (not oil-laden). Grouting of mortar, cement, or concrete.

Hose construction

Tube: abrasion resistant NR/SBR, black, smooth.

Reinforcement: two steel cords plies for ID 50 mm, four steel cords plies for other diameters.

Cover: abrasion and weather resistant NR/SBR, black, fabric impression.

Temperature range

-30 °C ÷ +80 °C

Couplings/Fittings

Swaged couplings with dimensions according to VICTAULIC or concrete pump manufacturers (PUTZMEISTER, SCHWING ...).



- Highly abras. resistant hose to give extended service life.
- Flexible and easy to handle.
- Robust construction to withstand heavy compressive loads to guarantee maximum safety.
- Construction eliminates kinking and allows easy cleaning by reverse pumping.
- Vacuum 0.8

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
TL5600057/20	50	66	85	170	2.14	200
TL5513037/20	65	85	85	170	3.41	200
TL5026062/20	76.2	100	85	170	4.8	250
TL5513038/20	85	109	85	170	5.38	270
TL5013893/20	101.6	128	85	170	6.85	280
TL5013895/20	125	153	85	170	9.2	340
TL5513039/20	150	179	85	170	11.33	500

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses